



AUTOMIG² i DIGITAL WELDING MACHINES FOR MODERN CAR REPAIR SHOPS

The Automig²-i range is designed for the auto business and light industries. User-friendly welding machines for MIG/MAG welding with or without double pulse and MIG brazing of galvanised steel plates; digital, synergic control panels with preset programs. DUO versions for easy switch-over between welding and brazing operations.



THREE POWER SOURCES - TWO CONTROL PANELS

THERE'S A MIGATRONIC AUTOMIG FOR EVERY GENERATION

Back in 1970, Migatronik supplied its first welding machine to the auto business. Since then, as many as seven welding machine generations have matched, each in their own way, the requirements made by the auto business and light industries. The Automig²i range is stronger than ever.

THE FULLY DIGITAL REVOLUTION - SWITCH ON, PRESS AND WELD

The Automig²i range are compact, fully digitised welding machines with synergic, preset welding programs and automated functions. The machines are designed for modern materials used in the auto business and meet the increasing demands for joining materials; from sheet metal to car body welding – with or without double pulse.

MACHINES WITH BUILT-IN ADVANTAGES

The Automig²i machines are equipped with four-roll wire feed system for precise and stable wire-feeding. The Automig² 273i features reversed polarity for welding with innershield wire (without gas).

MIG BRAZING

In addition to MIG/MAG welding, the Automig²i range features MIG brazing of galvanised steel plates. This function

ensures maintenance of the material in terms of corrosion and strength and reduces post-treatment of distortion of plates and profile tubes to a minimum. The result is cost-effective and efficient welding.

AUTOPULSTM WITH DOUBLE PULSE FOR WELDING AND BRAZING

The Automig² 273i is available with AUTOPULSTM control panel. This control panel features double pulse (DUO Plus) which is an advanced pulse function feeding the wire with a pulsatory current. The result is better control of the arc and a minimum of weld spatter which ensures preservation of strength and surface of plates and profile tubes.

BOOST FOR ALL MAINS VOLTAGES

The Automig² 273i and 273i DUO can be equipped with an electronic Boost Converter (autotransformer) for welding and brazing on all mono-phase and three-phase mains voltages.

DUO VERSIONS

The Automig²i machines are available in DUO versions with space for two wire reels: one for MIG brazing and one for other welding operations, making it easy to switch between welding jobs without having to change hoses, wires, wire drive rolls and gas.

USER ADVANTAGES

- Designed for all materials and individual welding applications
- Digital, synergic control panels
- Pulse or double pulse
- MIG brazing of galvanised steel
- AUTOPULSTM for advanced pulse welding and pulse brazing of e.g. high-tensile steel
- DUO versions for easy switch-over between welding and brazing operations
- Reversed polarity for welding with innershield wire (without gas)
- Boost versions for all mains voltages
- Software update via SD card at [migatronik.dk/MY MIGATRONIC](http://migatronik.dk/MY_MIGATRONIC)

Automig² 273i on trolley



Machine range/Panel	AUTOMIG II	AUTOPULS TM	Reversed polarity
Automig ² 183i	●		
Automig ² 183 i DUO	●		
Automig ² 233i	●		
Automig ² 233i DUO	●		
Automig ² 273i	●	●	●
Automig ² 273i Boost	●	●	●
Automig ² 273i DUO	●	●	●
Automig ² 273i DUO Boost	●	●	●

INDIVIDUAL VERSIONS FOR AUTO BUSINESS AND LIGHT INDUSTRY

MACHINE ADVANTAGES

- Compact design/low weight - user-friendly, flexible and mobile
- Standby function (15-30 W idling): energy-saving, less CO2 emission, long life of components
- Colour-coded wire drive rolls: easy to exchange
- Four-roll wire feed system for precise wire-feeding
- Digital motor control: stability under all operating conditions
- Digital fan control: optimal cooling under all operating conditions
- Lacquered PCB cards: less maintenance and longer service life



MIG-A TWIST® TORCHES

The ergonomic MIG-A Twist torch has a turnable swan neck for easy access to hard-to-reach locations. Control unit for adjustment of welding current at the torch handle is available as an optional feature.

The compact Automig² 183i



Automig² 273i DUO on trolley



AUTOMIG² i DATA & PROGRAMS

We reserve the right to make changes

POWER SOURCE	183i/183i DUO	233i/233i DUO	273i/273i DUO	273i BOOST/273i DUO BOOST
Current range, A	15-180	15-230	15-270	15-270
Mains voltage +/- 15%, V	3x400	3x400	3x400	3x230-400. 1x230-400
Fuse, A	10	10	10	16
Duty cycle 40°C 100%, A/V	115/19.8	165/22.3	175/22.8	107 (135)/19.4(20.8)
Duty cycle 40°C 60%, A/V	125/20.3	175/22.8	205/24.3	130 (170)/27.5(22.5)
Duty cycle 20°C 100%, A	160	220	230	150 (180)
Duty cycle 20°C 40%, A	180		245	
Protection class	IP 23S	IP 23S	IP 23	IP 23
Norm	EN/IEC 60974-1. EN/IEC60974-5. EN/IEC60974-10			
Dimensions (HxWxL), mm	660x380x790	660x380x790	550x250x640	550x250x640
Dimensions DUO (HxWxL), mm	960x600x850	960x570x870	960x570x870	960x570x870
Weight, kg	26.2 / 41.2	26.5 / 41.2	26 / 55	15-270

Automig II panel



AUTOPULS II panel



Both control panels can be updated via SD card with the latest program versions at migatronic.dk/MY MIGATRONIC.



PROGRAMS

Material	Wire Ø/mm	Welding	Brazing	Pulse	Double pulse (DUO Plus)
Fe SG 2	0.6 - 1.0	● ●		●	●
AL	0.8 - 1.2	● ●		●	●
CuAl8	0.8 - 1.0		● ●	●	●
CuSi3	0.8 - 1.0		● ●	●	●
CrNi	0.8 - 1.0	●		●	●

● AUTOMIG II panel ● AUTOPULS™ II panel

The list of programs is for guidance only

Svejsemaskinefabrikken Migatronic A/S
 Aggersundvej 33
 DK-9690 Fjerritslev, Denmark
 Tel: (+45) 96 500 600
 Telefax: (+45) 96 500 601
migatronic.com

